

The TRIMIG 200-4S is a « synergic » three phase welding unit, ideal for maintenance and locksmith work. It can weld steel, stainless, aluminium, and it is particularly suitable for intensive professional work up to  $\varnothing 1$ .

## PRODUCT

In « Synergic » mode, setting is fast and simple. The Micro processor controller will automatically set the optimum wire speed. This avoids complex set-up and ensures optimum welding parameters.

## 3 FUNCTIONS AVAILABLE

- **Normal**
- **Spot:** Spot welding with adjustable spot diameter
- **Delay:** « Chain spot » function (Spot welding with time adjustment between 2 spots).

## SYNERGIC MODE FOR EASY AND QUICK SETTINGS

- **With this function, the wire speed setting is Automatic.**

Simply select:

- the wire type
- the wire  $\varnothing$
- the power

TRIMIG 200-4S sets the optimum wire speed for you.

- **Save the last settings.**



- Included :
- 1 torch 250 A (3m)
  - Earth clamp (2m)



## ACCESSORIES
















### Torch MB25 kit (250A) (Not included)



Ref. 041233

Composition:

- Contact tips:
  - $\varnothing 0,8$  M6 steel/stainless (x 5)
  - $\varnothing 1,0$  M6 steel/stainless (x 5)
  - $\varnothing 1,0$  M6 Alu (x 5)
- Contact tips supports 250A (x 3)
- Springs for nozzle (x 5)
- Nozzles 250A (x 3)

															
50/60hz	10A	min▷max	GAS	NO GAS	100	200	300	Electronic Control	équipé d'origine / original equipment / originalausstattung / equipamiento de fabrica	EN60974-1 (40°C)	I <sub>a</sub> (60%)	X% (I <sub>2</sub> max)	U <sub>0</sub>	cm/kg	Protected & compatible POWER GENERATOR (+/- 15%)
400V 3~	10A	30-200A	0.6	-	-	✓	✓		0.8/1.0	1.0	140A	200A 30%	17V ▼ 34.5V	47x77x79 / 63	7.5 kVA